

GLY-COOL™ ADVANTAGE LIGHT DUTY

PRODUCT DATA SHEET

GLY-COOL™ LD NAPS FREE ELC/OAT COOLANT

Gly-Cool™ LD NAPS FREE ELC/OAT Coolant is precision blended to meet ASTM D-3306 standards. This coolant contains extended life corrosion inhibitors based on organic acids and provides maximum protection against damaging rust and corrosion in engine cooling systems. This inhibitor package is free of Nitrite, Amine, Phosphate and Silicate (NAPS FREE). This coolant does not contain 2-Ethyhexanoic Acid (2EH) nor any other organic acids that are aggressive to hoses and gaskets.

FEATURES

- Extended Life Coolant (ELC) provides a service life of 5-years/150,000 miles
- Applicable to both water only and glycol based coolants
- Does not contain Nitrite, Amine, Phosphate, or Silicate (NAPS FREE)
- Safe for all common elastomers used in hoses and gaskets
- A combination of many organic acids provides multi-metal corrosion protection, especially for aluminum
- Multiple scale inhibitors/dispersants.
- Convenient precision blended to 50/50, ready to use
- Non-Foaming

INDUSTRY STANDARDS

ASTM D-3306

ASTM D-4340 Hot Surface Aluminum Protection
ASTM D-1384 Corrosion Protection
ASTM D-2809 Water Pump Cavitation
ASTM D-1881 Foaming Characteristics
ASTM D-2570 Simulated Service Testing

Gly-Cool™ LD NAPS FREE ELC/OAT is for use in automotive light-duty trucks—American, European and Asian vehicles that require phosphate, silicate free coolants.

TYPICAL PROPERTIES	
Color	Pale Yellow
Specific Gravity	1.184
Approx. Density	8.9 lbs / gallon
Approx. PH	8.0 - 8.8
Freeze Point, °F	-34 min.
Boiling Point, °F	265 min.

RECOMMENDED APPLICATIONS

Compatible with major coolant types for top-off and service.

Chrysler
Ford
General Motors

Honda
Hyundai

Mercedes-Benz
Nissan

Toyota
Volkswagen



On-Site Antifreeze Recycling (Gly-Cool™ Advantage)
P.O. Box 3058, N. Fort Myers, FL 33918
800-872-9185
info@Recycle-Antifreeze.com
www.GLY-COOL.com